



**RamCAT5 & digital audio network system cable**  
**2x RamCAT5 + 2x digital audio**

- 2x RamCAT5-solid CAT5e data cable 4x 2x 0.52 mm (AWG 24/1)
- stabilizing PE cross
- SF/UTP (overall foil + braid shield)
- PVC element jackets, Ø 6,6 mm
- 2x digital audio cables, 110 Ohm, AWG 24
- EtherSound™ tested by Digigram up to 120 m



This system cable with 2x CAT5 and 2x AES/EBU was developed for mobile audio networks (e.g., for the connection of Stage Racks with the Allen&Heath iLive mixers which need 2 Cat5 cables). As a 2-fold network cable element the especially robust, double shielded and windable RC5SB is used. Thanks to solid AWG24 conductors it allows EtherSound™ up to 120 metres. The suitability for the mobile use is reached by the special construction with a cross-shaped twisting element. Two additional digital audio cables (AWG 24, 110 Ohm) allow additional functions such as Intercom, monitoring, serial remote control etc.

**hybrid**

twisting	2x data + 2x audio
taping	fleece
outer jacket	PVC
overall diameter	16.4 mm

**audio cable**

cond. construction	stranded tinned copper, 7x 0.20 mm (AWG 24/7)
cond. cross section	0.22 mm <sup>2</sup>
insulation	foam-skin PE, red & blue
shielding	tinned stranded drain wire + AL/PETP foil
outer jacket	PVC, grey, numbered, Ø 4.0 mm
conductor resistance	< 85 Ω/km
capacitance	47 pF/m
characteristic impedance	110 Ω
nom. attenuation [dB/100m]	
1 MHz	2.3
3 MHz	3.9
10 MHz	6.9
insulation resistance	> 10 GΩ x km
test voltage	
cond. / cond.	1200 V
cond. / shield	500 V

**data cable**

conductor	solid bare copper wire, Ø 0.52 mm (AWG 24/1)
core insulation	foam-skin PE
core stranding	2 cores twisted to a pair
cable stranding	4 pairs twisted within a central PE cross
overall shield	AL/PET foil + tinned copper braid (80% coverage)
outer jacket	PVC
outer diameter	6.6 mm
conductor resistance	< 85 Ω/km
mutual capacitance	48 pF/m
characteristic impedance	100 Ω ± 15%
signal speed	0.76 c
propagation delay	4.9 nsec/m
delay skew	0.25 nsec/m

**mechanical & thermal characteristics**

working temperature	
mobile use	-30°C / +75°C
installation	0°C / +50°C
min. bending radius	
mobile use	12x overall diameter
installed	8x overall diameter
no hazardous substances	acc. to EU directive RoHS 2011/65/EU from 08.06.2011
CE conformity	acc. to EU directive LVD 2006/95/EG
flame retardancy	acc. to IEC 60332-1-2

frequency [MHz]	attenuation [dB/100m]		Next [dB]		ACR [dB/100m]		RL [dB]	
	typical	CAT5e MAX	typical	CAT5e MIN	typical	CAT5e MIN	typical	CAT5e MIN
1	2.0	2.1	85	65	83.0	62.9	26	-
4	3.9	4.0	74	56	70.1	52.0	28	23.0
10	6.1	6.3	70	50	63.9	43.7	30	25.0
16	7.8	8.0	68	47	60.2	39.0	30	25.0
20	8.7	9.0	63	46	54.3	37.0	30	25.0
31.25	10.9	11.4	58	43	47.1	31.6	28	23.6
62.5	15.9	16.5	55	48	39.1	31.5	26	21.5
100	20.6	21.3	52	35	31.4	13.7	24	20.1
155	24.8	-	49	-	24.2	-	21	-
200	29.3	-	46	-	16.7	-	19	-

order code	type	outer jacket	cable color	weight kg/m	standard lengths m
RC5-SB2A	SF/UTP + AES/EBU	PVC	black	0,29	50 / 100 / 300

technical specifications are subject to change