




## technical specifications QRP20/90

### general

- Point-source column with high-Q directivity for increased projection control
- RBN401 pro-ribbon HF driver with exceptional intelligibility and “throw”
- 1:1 non-compressed linear sound reproduction, with up to 90% less distortion
- Fully symmetric and coherent horizontal and vertical pattern control
- Woofers with Active Coil™ technology for further reduced LMF distortion
- SIS™ pre-wired for very high system damping and further reduced distortion



### description

The QRP20/90 is a 2-way column loudspeaker to be used as vertical sound system, for both permanent and portable applications. Its slim design packs a perfectly natural, dynamic sound reproduction with superb intelligibility, coverage and throw.

It is specifically designed for applications where ultimate fidelity response needs to be projected with wide horizontal and narrow vertical coverage, ideal in acoustically challenging environments, or applications where intelligibility-over-distance is required.

Loaded with the RBN401 4” pro-ribbon driver on a “Morpher” lens, the system offers an exceptional, SPL-independent throw-efficiency and projection control, due to the pro-ribbon’s all-natural cylindrical (isophasic) wavefront.

The patented (90-degrees) horizontal dispersion offers a wide and consistent audience coverage up to the highest frequencies.

Its fast impulse response, “compression-less” principle and unusual high peak power handling (800W @ 200ms) cater for a perfect intelligibility from the lowest to the highest SPL with a 1:15 dynamic range, while offering a maximum “gain-before-feedback”.

The RBN401 driver is mounted in a D’Appolito speaker configuration with four woofers in a sealed cabinet. The custom-design 5” woofers feature Active Coil™ technology for extremely low-distortion LF reproduction, a perfect match with the MHF pro-ribbon technology.

The frequency response roll-off enables an excellent partnering with an additional subwoofer.


The system brings the unsurpassed clear, dynamic and ultra-low distortion Alcons signature sound in a very slim and unobtrusive package; The M10 mounting points on top and bottom and the M6 universal mounting bracket pattern on the back, together with the optional ACO™ color scheme provides for an inconspicuous, low-profile presence in any application.

The QRP20 is powered and controlled by the ALC amplified loudspeaker controller; Through the integrated VHIR™ processing, audiophile amplifier stages and Signal Integrity Sensing™ feedback circuit, the ALC offers QRP20-specific drive processing, delivering absolute maximum sound quality with increased headroom and utmost operation reliability and flexibility.

The QRP20 is available in two versions with 90-degree (QRP20/90) and 120-degree (QRP20/120) horizontal dispersion.

## technical specifications QRP20/90

### dimensional drawing



### technical specifications

Frequency response	72 Hz - 20.000 Hz	(+/- 3 dB)
	64 Hz -	(+/- 10 dB)
Sensitivity nominal	99 dB (200 Hz - 10 kHz)	
Nominal impedance	4 ohms	
Recommended drive	Sentinel3 min.	
Nominal SPL peak	128 dB (Sentinel3 200 Hz - 10 kHz)	
	133 dB (Sentinel10 200 Hz - 10 kHz)	
Dispersion H x V	90° x 15° (@20kHz)	

### physical specifications

System	2-way, full-range	
Filtering	passive	
Drivers LF	4x AMB5NDAIC-16 5", sealed	
Drivers HF	1x RBN401 4" pro-ribbon driver	
Connectors	2x Speakon NL4 input/link	
Physical dimensions	mm	inches
Height	742	29.2
Width	150	5.9
Depth	150	5.9
Weight (approx.)	kg	lb
	12	26.5
Warranty	6 years limited	

A: Alcons Audio  
De Corantijn 10  
1689 AP, ZWAAG  
The Netherlands

E: [info@alconsaudio.com](mailto:info@alconsaudio.com)  
W: [www.alconsaudio.com](http://www.alconsaudio.com)  
T: +31 (0)229 28 30 90